The River Machine: A Conceptual Model Integrating Fish Movement and Habitat, Fluvial Geomorphology, Fluid Dynamics, and Biogeochemical Cycling

John Nestler

IIHR—Hydroscience & Engineering, University of Iowa, USA and

David Smith and R. Andrew Goodwin

U.S. Army Engineer Research & Development Center Vicksburg, Mississippi 39180 USA


and many others

Thinking about Fish at Ecosystem Scales Presentation Organization


- Hydrodynamic variables used by juvenile salmon during emigration
 - Velocity Magnitude Gradient (cue) and Velocity Magnitude (direction)
 - Huge tagging data sets from Pacific NW USA emigrating salmon / not likely to be duplicated
 - Salmon good model system for understanding fish movement
 - Goodwin et al. 2006
- These two variables used by fish to create a "hydraulic road map" in unimpaired streams
 - Two variables integrated together (+scale) relate to the solid features in a channel
 - Fish form a "hydraulic snapshot" of their surrounds to choose direction or location
 - Nestler et al. 2008


Cues are related to fluvial geomorphology and biogeochemical cycling


- Migrating fish locate in time and space to take advantage of work performed by the river i.e., they find biogeochemical hotspots and hot moments (River Machine Concept).
- Nestler et al. 2012



The Method: Integrate Eulerian, Lagrangian, & Agent-Based Frameworks = ELAMs









Operationally.....

Computational mesh

Stimulus (Cue) Categories:


- > Hydrodynamic
- > Water quality
- > Electrical fields
- Visual (foraging)





Sensory ovoid

Separate Passive Transport & Volitional Swimming & Determine Swim Direction



"Governing Equation" for Short Time Steps:

New Position_x = Old Position_x + passive transport_x + ε_x + biases_x + volitional swimming_{orientationi} +

^Eorientation

Orientation_i= α_1 + β_1 *(velocity) + β_2 *(acceleration) + β_3 *(turbulence intensity) + β_4 *(turbulence dissipation) + β_i *(other hydraulic variables) + β_j *(secondary variables)

(0.65 * Var) + (0.35 * RN)

i,j,k

Fish Track comprised of Observations (pings) 1-8


Volitional swimming_i= α_1 + β_1 *(velocity) + β_2 *(acceleration) + β_3 *(turbulence intensity) + β_4 *(turbulence dissipation) + β_i *(other hydraulic variables) + β_i *(secondary variables)


DV=
$$\alpha$$
 + (β ₁ x INDV1) + (β ₂ x INDV2) + etc
Where :
DV= a + b + c + d
INDV1= a + f + g + q
INDV2= a + v + c + q


Spurious Auto-Correlation Non-independent Variables Serial Auto-Correlation





Discriminate Analysis














Calibration Approach:


- 1 Match salient features of individual traces
- 2 Refine with passage percentages





How Well Does it Work?






All Dams
(LGR, IHD, TDA, WAN, PRD)






- What Causes Flow Pattern in Streams?
 - Flow Resistance without it there is nothing to change a unit volume of water once it is set into motion by gravity.
- > Are There Different Types of Flow Resistance?
 - Four total, but two for steady-state
 - Friction resistance (skin friction)
 - Form resistance (distortion resistance)
- ➤ Minimum Hydraulic Information Separating Q Resistance?
- > Should lead to conceptual model for movement cue.

Behavioral Rule & Natural HydroGeomorphology





K₄=Coefficient identifying S threshold for wall bound flow

K2=Coefficient identifying S threshold for free shearflow detection, Note: K2>>K1

Fish sensory sensitivity addressed using signal-to-noise analogy as ΔS/S at each time step.

Acclimation calculated by adjusting signal and noise to sequential conditions (ambient) encountered by virtual fish as ΔS-S_{ambient}/S-S_{ambient} using a memory coefficient to discount past information relative to newer information.

Acclimation term allows virtual fish to adjust behavior as flow field pattern and energy change over time (i.e., as discharge changes) or space (i.e., as migrating fish encounters channel morphology changes).

Apply to Different System - Mississippi

• Concrete portion is 373.1 m long with three roller gates and ten tainter gates.

• Submersible earthen dike 487.7 m long connected to levee.

• Main lock is 33.5 m wide by 182.9 m long


• Incomplete auxiliary lock.






Proposed fish ladder

- 61 m bottom width, 152 m total length
- 1.5 m deep pool
- 0.6 m deep, 0.3 m drop riffles
- 1.5 m diameter boulders at 1.2 to 1.8 m spacing
- Rule changes default swim u/s / weak attraction to VMG






Telemetry





- 155 shovel-nosed sturgeon were tagged with Vemco acoustic tags (Tripp and Garvey 2011)
- Over four years, ~60% of the sturgeon detected downstream were detected upstream. Most were thought to pass the dam during the spring time.
- Observed to concentrate in eddy near dam and along east shoreline

Scenarios


- Five flows (90% to 10% exceedance)
- Three configurations
 - Existing dam with no ladder
 - Existing dam & proposed ladder
 - Constant 1.49% of river flow (16.6 to 85.8 cms)
 - No dam & existing levied channel
- All gates open with equal flow
- 500 fish output at 10 second time step
- Descriptive statistics
 - Path length (m)
 - Swim speed (BL/s) (Hoover et al. 2011
 - Fatigue (%) (Katapodis and Gervais 2011)
 - Swim angles (degrees)
 - Spatial distribution
 - Passage (%)







Pattern in Passage Results - Useful Results



Interim Conclusions

Seems to Have Worked – juvenile salmon & adult sturgeon passage applications successful

Therefore:

- "Solution Space" continues to feature velocity magnitude and velocity magnitude gradient with accommodations for fish size, model dimensionality & mesh attributes in a nonlinear manner.
- Limited number of upstream / downstream movement strategies / reduces study needs





(Slope => Applied Force):


What the Machine Does: 1) Erosion/Deposition driven by shear (strain – VGM)

2) Transport/residence time driven by velocity magnitude

Creates immense temporally variable, spatial complexity







Monthly Hydrograph São Francisco River, BR

Hydrologic & Fisheries Characteristics of Three Floodplain Reaches São Francisco Basin, Brazil

Summarized from Sato & Godinho 2003; Pompeu & Godinho, 2006; Santos, 2009; Santos et al, 2009

	São Francisco River Floodplain regions		
	Lower Velhas River	Middle São Francisco River	Lower São Francisco river
Elevation	490-510 m	430-500 m	10-90 m
Number large reservoirs upstream	zero	one	eight
Flow regulation	insignificant	moderate	severe
Floodplain fish biodiversity	61 species	48 species	48 species
Large migratory fish extinction?	no	no	yes
Status of fisheries	No information	decreased catches	decreased catches

Reconciling Fish Habitat Concepts: Small Streams and Large Rivers



Place-Specific (resident) Activity

- Feeding at a feeding station
- Spawning at a specific area



Local Hydraulic Variables

- Absolute values critical
- Background less important

Place-Searching (Itinerant) Activity

- Locating a new feeding station
- Locating resource caches
- Finding a spawning site

Roadmap Hydraulic Variables


- Absolute values less important
- Background very important

Resident fishes in small, hardbottom, baseflow streams: e.g, darters, sculpins, trout Nu<mark>ldSli&aSFright</mark>e Su**ldyglate**ilic Mo**ldels**itat Tools Mobile fishes in large, flood pulse rivers: e.g, sturgeon, paddlefish, salmon


Aristotle and First Principles ELAMs and HSI Curves







NHG Approaches – Empiricist "Not very incremental"









Image: Control of the control of the

The "River Machine", Function, Process, Large River Fishes, and Disturbance



River Machine & Hydrologic Engine: Machine Supports Immense abundance and diversity of life

- Illinois River One of worlds most productive fisheries
 - provided portion of protein needs of Chicago
- Mekong River catch of ~2M metric tons
 - provides protein needs of ~200,000 people
- Parana River catch of 1,000 kg/hectare of sabolo

Fluvial Dependent Fishes take advantage of the "free" work performed by the river

- couple their biology to basin processes
- access to hundreds of millions of tons of organic matter produced in large river basins / watersheds
- other taxons use this strategy?



"River Machine" Concept Ramifications

- Pragmatic ramifications if true:
 - Same movement rule for all species (+secondary currents), with nuances for swimming speed & size, channel orientation (e.g., surface, thalweg, shoreline), fish anatomy & physiology, etc.
 - Reduces study needs to develop hydraulic criteria for fish passage design
- Conceptual ramifications if true apply to:
 - Environmental flow determination
 - Channel restoration actions
 - Nutrient management goals
- Goal test the "River Machine" concept using the existing rule & calibrating/validating to a completely different species (shovel nose sturgeon Scaphirhynchus platorynchus) and site (Mississippi River) using fewer data.

Why Engineers & Ecologists Must Collaborate Philosophical / Conceptual / Scientific Reasons

> "....in seeking regularity and focusing on the most salient features in their environment, in order to endure and thrive, animals have empirically discovered the laws (i.e., physical) of nature."

(Kalmijn, A. J. (2000). Detection and processing of electromagnetic and near-field acoustic signals in elasmobranch fishes. Philosophical Transactions of The Royal Society of London series B, 355(1401), 1135-1141.)

- Ecologists accurately describe/predict ecological response
- > Engineers accurately describe/predict flow fields
- > Understanding how animals "endure and thrive" requires integration of tools from both disciplines accurate forecasting requires seamless integration

Conclusions

Seems to Have Worked –

Successfully calibrated to tagging data, matched observations, and got insightful results

Therefore:

- "Solution Space" continues to feature velocity magnitude and velocity magnitude gradient with accommodations for fish size, model dimensionality & mesh attributes in a nonlinear manner.
- Limited number of upstream / downstream movement strategies / reduces study needs
- River Machine concept supported at least for fluvial dependent large river fishes
 - Fish Passage
 - River Restoration
 - Nutrient Management Approaches
 - Good Supplement / Alternative for HSI-based tools

Thank you!



Questions? Comments?

Note: No animals were harmed or killed In the preparation of this presentation